



# DIGITAL IMAGE MULTI CAREER INFORMATION CONCEALING ALGORISM BASED ON DIGITAL IMAGE FUSION FEATURES

**HASSAN YAHAYA, UKASHATU BARAU, YUSUF AHMAD**

*Department of Office Technology and Management, Department of Quantity Surveying  
Abdu Gusau Polytechnic Talata Mafara, Zamfara State*

## **Abstract**

*Multi-source image fusion is a research topic that combines sensor, computer image processing, artificial intelligence, and other fields with images as its object in multi-source information fusion. The study overview and novel concepts based on the multi-resolution decomposition and fusion approach were the key topics of this article. Using variational partial differential equations to explore the merger of regional and multi-resolution data at the feature level. The specific use of multiple source picture feature level fusion in road target detection, and how to achieve the objective evaluation of image fusion performance.*

**Keywords:** Computer image technology, sensor technology, and multiple image fusion.

## **Introduction**

More and more sensors are being used in numerous fields as image sensor technology advances. The quantity of data gathered and the variety of information presented rise quickly as the number of sensors increases. The new needs cannot be addressed using conventional information processing techniques. Therefore, in this situation, multi-source information fusion technology appears at just the correct time. In order to gain more plentiful, accurate, and trustworthy helpful information, multi-source information fusion refers to carrying out a thorough processing with many levels, multiple aspects, and numerous layers of the multi-source information from different sensors. Its major goal is to combine two or more source photos with supplementary or redundant features into a new image by using a specific algorithm. Make the image after fusion as clear and understandable as possible by making the most of complementary information and reducing redundancy. Multi-source picture fusion is the full processing of data across several carriers to fulfill a certain objective. Multi-source picture fusion has a very broad use. This approach can be described as a multi-source image fusion. After combining and abstracting various exceptional situations, the general conclusion is reached. As a result, inductive reasoning and information fusion are inextricably linked. And all science and technology are the result of inductive reasoning. Multi-source picture fusion has gained significant attention in many domains recently, and the technology behind it has advanced quickly.

## **Technology for Multiple Image Fusion**

Currently, optical, radar, and infrared imaging make up the majority of the imaging sensor. Due to its abilities to penetrate smoke and work around double tides, infrared imaging is especially valuable in close-range imaging tracking systems. Although active radar imaging sensors can operate in all weather, their extensive equipment and complicated design limit their use in many situations. Additionally, ground clutter has a significant impact on radar images. A visible light CCD imaging system has a small, straightforward structure, excellent resolution, and good anti-jamming capabilities, although it is more susceptible to weather changes. Multi-source image fusion, in contrast, integrated sensor, digital signal processing, artificial intelligence, and other fields. Its major goal is to combine two or more source photos with supplementary or redundant features into a new image by using a specific algorithm. Make the image after fusion as clear and understandable as possible by making the most of complementary information and reducing redundancy. Additionally, it can provide more useful information for subsequent image processing tasks such image segmentation, object detection, recognition, and evaluation of battle damage. Fig. 1 combines redundant and additional information from the original photos. Multi-source picture fusion creates a new image with more value information rather than just a simple superposition. Not only may photos from the same type of sensor be combined, but also images from other types of sensors. However, a sensor of the same kind has the same physical significance, and photographs have the same characteristics. Images from various sensor types have a higher degree of complementarity, making the significance of the fusion of heterogeneous images clearer.

## **BASIC CONCEPT, SYSTEM ARCHITECTURE, AND MULTI-SOURCE IMAGE FUSION ALGORITHM**


### **Multi-source Image Fusion's Fundamental Principle and System Structure**

With the integration of sensors, signal processing, image processing, and artificial intelligence, image fusion is a new technology. Image preprocessing, picture registration, image fusion, feature extraction and recognition, and decision-making make up the general processing flow of multi-source image fusion. Multi-source image fusion is typically divided

into three levels: pixel level fusion, feature level fusion, and decision level fusion [5]. These levels are based on the stage of fusion in the processing flow and the degree of information abstraction. Fig. 2 depicts the decision level fusion frame structure.

### Algorithm classification

Six different forms of multi-source image fusion algorithms exist: linear weighted fusion, false color image fusion, modulation-based picture fusion, statistics-based image fusion, neural network-based image fusion, and multi-resolution decomposition-based image fusion.



## FUSION OF MULTIPLE SOURCE IMAGES USING MULTIPLE RESOLUTIONS

### Orthogonal Wavelet Transform, Section 4

Each subspace can be projected with a digital signal from space. In many situations, analyzing the signal projection in each subspace is much simpler than analyzing the original signal. Displays a signal multi-resolution analysis reflected in frequency space.




Fig. 1 Multi-resolution frequency separation characteristics

Decompose the original signal into two sub-bands using a high-pass filter (g) and a low-pass filter (h). Then, to further decompose the low frequency sub-band, employ recursively low-pass and high-pass filters [6]. Fig. 4 illustrates the realization of the aforementioned multi-resolution decomposition using a series of the FIR filter bank.




Fig. 4. Parse tree of filter bank for multi-resolution analysis.

If  $t \in L^2(\mathbb{R})$  meets

the "permissible" condition: then  $t$  is called a basic wavelet. For a basic wavelet  $t \in L^2(\mathbb{R})$ , square integrable space function  $f \in L^2(\mathbb{R})$ , its wavelet transform definition is:  $W_{t,b}(a,b) = \int_{-\infty}^{\infty} f(t) \overline{t(a^{-1}(t-b))} dt$ ,  $(a,b) \in \mathbb{R} \times \mathbb{R}$ ,  $a > 0$  is the scale factor, reflects the displacement, its value can be positive or negative,  $t$  is the continuous variable.

Therefore, it is known as the continuous wavelet transform.

Discrete wavelet  $\psi_{j,k}(t)$  is

$$\psi_{j,k}(t) = a_0^{-j/2} \psi(a_0^{-j}t - k), \quad j \in \mathbb{Z}, k \in \mathbb{Z} \quad (2)$$

In the family of orthogonal wavelets structured by Duchies, the decomposition and reconstruction filter group are shown in Fig. 5.

### Enhancing Multi-Spectral Images Using Biorthogonal Multiwavelets

The evolution of unit-wavelet theory is multiwavelet theory. Multiwavelet has more structural freedom and can simultaneously satisfy the needs of orthogonality and symmetry. The biorthogonal multiwavelet is produced if two biorthogonal bases are used in place of an orthogonal basis. Two mutual dual scaling functions make up each of the two biorthogonal bases. One for the breakdown and the other for the rebuilding. Still meet the double dimension equations as follows for each scale function  $\phi(t)$  and the corresponding wavelet function  $\psi(t)$

$$\phi(t) = \sum_k C_k \phi(2-t-k) \quad (7) \quad \psi(t) = \sum_k D_k \psi(2-t-k) \quad (8)$$

Biorthogonal multiwavelet is structured on the basis of ordinary GHM orthogonal multiwavelet, as shown in Fig. 7.





Fig. 7. Biorthogonal multiwavelet (GHW base) scale function

Widespread interest is drawn to the beneficial properties of multi-resolution analysis in signal analysis in the context of picture fusion. The majority of the fusion algorithm is currently developed using a multiresolution analytic framework. The primary area of research in the subject of image fusion is the multi-resolution analysis-based image fusion approach [7]. In this chapter, we present a method for multi-spectral picture enhancement that combines the features of the biorthogonal multiwavelet transform with the fusion strategy of choosing low frequency coefficients. Using several resolution analyses, image fusion is being attempted. On the other hand, having in-depth understanding of the framework for implementing picture fusion based on multiresolution analysis is a basis for future study in the field of image fusion.


### Features of the Optical System Imaging

The system function band width for a blurred image is smaller than that for a highly focused image. The general features of the optical imaging system are depicted in Fig. 8.



### Model of Color Fusion

Fig. 9 displays the color fusion model based on the HSV color space. A cone can be used to represent the HSV color space. It has three parts, labeled V (Value), S (Saturation), and H, respectively (Hue). They are apart from one another. H stands for the angle generated by rotating the cone's central axis in the range of (0, 360), in the colors red, yellow, green, and blue, before switching back to red. The range of Saturation S, which is dependent on the ratio of the composition's with-color and decolorization components (gray) (0, 1). The degree of saturation increases with the size of the color combination. The degree of saturation decreases as the decolorization composition increases. V can be thought of as a description of a color image on the domain of gray levels, which contains the primary spatial features of a color image.



### Fusion Model of Color Multi-Focused Image.

To solve the problem of color distortion, we put forward triangle average algorithm based on significant weighted. Tonal component of k band source image is denoted by  $H_k$ , and Synthesis of tonal component  $H_R$ , then:

$$HR = \sum_{k=1}^N \cos(H_i) \sum_{N=1}^N S_k$$

This approach to color component processing can successfully prevent color distortion. Any number of color source image fusions can use it. When seen from the standpoint of the spatial domain, the picture observer realizes the visual information through the alteration of the image contrast, which is the edge or gradient of the image. Therefore, based on the strength of the characteristic diagram, we design different weights according to the significance of various features that are reflected in the source image. Calculate the principal component as the target gradient field of the fusion and weight it in accordance with the contrast information of the source picture. So as to actualize the image fusion of characteristic keeping. To calculate fusion results, close to the objective, a variational problem is then employed to create a special contrast in advance to serve as the target of the fusion.

## FUSION OF MULTIPLE SOURCES BASED ON REGION

### Graph Theory-Based Image Segmentation

Define a metric area  $R_1$  and  $R_2$ , with a boundary predicate:

$D(R_1, R_2) = \begin{cases} \text{true} & \text{if } RD(R_1, R_2) \leq MID(R_1, R_2) \\ \text{false} & \text{otherwise} \end{cases}$  Of which,  $RD(R_1, R_2)$  represents the difference between  $R_1$  and  $R_2$ , denoted by:  $MID(R_1, R_2) = \min(ID(R_1) + k / R_1, ID(R_2) + k / R_2)$  (18)


Internal differences of  $R$  are denoted by  $ID(R)$ , Greatest weight edge  $e$  of minimum spanning tree in  $R$  is:  $ID(R) = \max_{e \in MST(R)} w(e)$  (19)

Regional image obtained by the source image segmentation generates a joint area image as follows:


### Fusion Strategy Based on Multi-Scale Decomposition and Regional Characteristics

In computer vision research, multi-scale decomposition simulates how the human eye perceives objects. The image is broken up into multiple scales from bottom to top. Each layer of the image is created by filtering the previous layer using a template. Additionally, multi-scale decomposition can efficiently carry out numerous simple image operations and generate a collection of low pass or band pass images. The relationship between local and global processing is made possible by the interconnection between the layers. Therefore, combining multi-scale decomposition with regional fusion approach characteristics will improve fusion impact.


A useful technique for multi-scale breakdown is wavelet analysis. Discrete wavelets are frequently used in fusion to create multi-scale decomposition. Biorthogonal multiwavelet is chosen to do multiscale decomposition because it has superior signal processing qualities such limited support set, orthogonality, symmetry, and vanishing moment. We proposed a fusion technique based on the biorthogonal multiwavelet that combines regional characteristics with multi-scale decomposition, as illustrated in Fig. 11.



(a) Regional Segmentation Image of Source Image1.



(b) regional segmentation image of source image2.



(c) Synthetic regional figure

Fig. 10. Generating sample of synthetic regional figure




Fig. 11. Fusion algorithm flow with a combination of regional characteristics and biorthogonal wavelet decomposition.

Different fusion criteria are required in the fusion process because to the physical differences between scale coefficient and wavelet coefficient. The significant shift in gray level is represented by the point with a bigger absolute value in the wavelet coefficient. which regions of the image have edges, linear characteristics, and boundaries. The source image is roughly represented by the scale factor. It might pick up some of the

source image's texture and grayscale traits. The scale coefficient of the composite image in many fusion methods is therefore often the weighted average of the scale coefficient of the source image. Wavelet coefficients are combined only when necessary.

### Compatibility Test

Similarity of area  $R_l$  of source image A and B is denoted by  $M(R_l)$ , then:

$$M(R_l) = \frac{2 \sum_{x,y \in R_l} [C_A^l(x,y) \cdot C_B^l(x,y)]}{S(A,R_l) + S(B,R_l)} \quad (20)$$

$$S(I, R_l) = \sum_{x,y \in R_l} [C_I^l(x,y)]^2, \quad I = A, B \quad (21)$$

In the case of low similarity, points with larger coefficient values in the source image should be converted into the composite image. When similarity is high, make average of the coefficient value of the source image. Similarity threshold is denoted by T. When  $T \leq M(R_l)$ ,  $C^l(I, R_l) = \{C^l(A, R_l) \text{ if } S(A, R_l) \geq S(B, R_l), \text{ otherwise } S(B, R_l)\}$  (22) When  $T > M(R_l)$ ,  $C^l(I, R_l) = \{w_{\max}(R_l) \cdot C^l(A, R_l) + w_{\min}(R_l) \cdot C^l(B, R_l), \text{ if } S(A, R_l) \geq S(B, R_l) \text{ else } w_{\min}(R_l) \cdot C^l(A, R_l) + w_{\max}(R_l) \cdot C^l(B, R_l)\}$  (23) Of which,  $w_{\max}(R_l)$  and  $w_{\min}(R_l)$  are respectively the maximum and minimum coefficient weight, defined by:  $w_{\min}(R_l) = 1 - 1/(1 - M(R_l))^{\max l \min l}$  (24),  $w_{\max}(R_l) = 1 - w_{\min}(R_l)$

The threshold value is modest overall. Because a tiny threshold is more compatible with the human visual system when the source image's resemblance is low. In image fusion, individuals frequently pay more attention to the image of the actual goal or area than a single pixel. Additionally, source picture noise and source image registration accuracy have a significant impact on pixel-based fusion. While more flexible fusion strategies can be proposed in accordance with target or regional features and successfully retain considerable information of source picture, region-based feature level fusion approach is not susceptible to these influences.

### Finalization

As computer science and microelectronics technology advance quickly, more and more sensors are being used in a variety of industries. And as the number of sensors has expanded, the amount of data that has been received has greatly increased and now exhibits diversity. The old methods of information processing are already unable to meet the increased demands. Therefore, the technology of multi-source image fusion is suggested. In the world of picture application, multi-source image fusion technology has long been recognized as a very valuable processing technique. Subjective assessment, or the visual evaluation method, has become a primary method of evaluating the quality of multi-source image fusion as demand has increased. There are essentially three layers involved in the realization of multi-source image fusion: pixel level, feature level, and decision level. The most extensive and in-depth of which is the pixel level fusion research. There are primarily six methods of implementation: linear weighted fusion, fusion of false color images, fusion based on modulation, fusion based on statistics, fusion based on neural networks, and fusion based on multi-resolution decomposition. This essay provides a brief analysis of a few fusion methods.

The study has demonstrated that the currently used fusion method can successfully address a variety of picture fusion-related issues, and some useful systems have been created.

## References

- A. A. Goshtasby (2007). Image Fusion: Advances in the state of the art, Information Fusion, Vol. 8, Issue 2, 2007, pp. 114-118.
- G. Simone, A. Farina, F. C. Morabito, et al. (2002). Image fusion techniques for remote sensing applications, Information Fusion, No. 3, 2002, pp. 3-15.
- Liu Gang, Jin Zhongliang, Sun Shaoyuan (2005). Image fusion based on the expectation maximum algorithm, Laser & Infrared, Vol. 35, Issue 2, 2005, pp. 130133.
- Liu Yanyan (2006). Research on key technologies in multisensor data fusion, China Science and Technology University, 2006.
- Ni Guoqiang (2001). Research and new development of multi-band image fusion algorithm, Optoelectronic Technology & Information, Vol. 14, Issue 5, 2001, pp. 11-17.
- Wang Haihui, Peng Jiaxiong (2004). Image fusion based on multiwavelet transform, Journal of Image and Graphics, Vol. 9, Issue 8, 2004, pp. 1002-1007.
- Yao NAN, Wang KAISHENG, Yu JIN (2013). Study on Fusion Algorithm of Multi-source Image Based on Sensor and Computer Image Processing Technology: <http://www.sensorsportal.com>© 2013 by IFSA